


D ≤ 5,5

DIN 1835B

 $\lambda = 30^\circ$ $\gamma = 8^\circ$

typ

N

HSS
Co8

Uygulama / Usage / Applikation / Zastosowanie

1 2 3 4 5 6 7 8 9 10 11 12 13

D k 10	l	L	d h 6	Z	CODE
3	12	56	6	4	121518.030
3,5	15	59	6	4	121518.035
4	19	63	6	4	121518.040
4,5	19	63	6	4	121518.045
5	24	68	6	4	121518.050
5,5	24	68	6	4	121518.055
6	24	68	6	4	121518.060
7	30	80	10	4	121518.070
8	38	88	10	4	121518.080
9	38	88	10	4	121518.090
10	45	95	10	4	121518.100
11	45	102	12	4	121518.110
12	53	110	12	4	121518.120
14	53	110	12	4	121518.140
16	63	123	16	4	121518.160
18	63	123	16	4	121518.180
20	75	141	20	4	121518.200
22	75	141	20	5	121518.220
24	90	166	25	5	121518.240
25	90	166	25	5	121518.250
26	90	166	25	5	121518.260
28	90	166	25	5	121518.280
30	90	166	25	5	121518.300
32	106	186	32	6	121518.320
36	106	186	32	6	121518.360
40	125	205*	32*	6	121518.40032

*/ ≠ DIN 844

Sipariş örneği / Example of order / Bestellungsbeispiel / Przykład zamówienia: **121518.060** (+ TiAIN)